

Accessories / LED Bulb LED Bulb 115VAC E27 Ø45x75



Part No.: 956.050.67

MECHANICAL DATA	
Length	75 mm
Diameter	45 mm
Weight with packaging	29 g
Product weight	15 g
ELECTRICAL DATA	
Operating voltage	115V
Operating voltage type	AC
Operating voltage frequency	60Hz
Operating voltage tolerance	+/- 10%
Rated operational voltage	115 VAC
Rated operational current	35 mA
Power illuminant	2 W
OPTICAL DATA	
Light source	LED
Light colour	White
Optical signal image	Permanent
Lamp fitting/socket	E27
APPROVAL DATA	
Conforms with CE	No
Conforms with RoHS directive	Fulfills substance restriction
WEEE	No
	NO
Conforms with ATEX-directive	No
Conforms with ATEX-directive Conforms with CCC-Ex	
	No
Conforms with CCC-Ex	No No
Conforms with CCC-Ex Conforms with CCC	No No No
Conforms with CCC-Ex Conforms with CCC Conforms with UL	No No No
Conforms with CCC-Ex Conforms with CCC Conforms with UL Conforms with FCC	No No No No
Conforms with CCC-Ex Conforms with CCC Conforms with UL Conforms with FCC Conforms with IC	No No No No No
Conforms with CCC-Ex Conforms with CCC Conforms with UL Conforms with FCC Conforms with IC EAC certificate available Conforms with UKCA (Importer) Conforms with CMIM	No No No No No No
Conforms with CCC-Ex Conforms with CCC Conforms with UL Conforms with FCC Conforms with IC EAC certificate available Conforms with UKCA (Importer)	No No No No No No No
Conforms with CCC-Ex Conforms with CCC Conforms with UL Conforms with FCC Conforms with IC EAC certificate available Conforms with UKCA (Importer) Conforms with CMIM	No No No No No No No No
Conforms with CCC-Ex Conforms with CCC Conforms with UL Conforms with FCC Conforms with IC EAC certificate available Conforms with UKCA (Importer) Conforms with CMIM Conforms with AS-I	No
Conforms with CCC-Ex Conforms with CCC Conforms with UL Conforms with FCC Conforms with IC EAC certificate available Conforms with UKCA (Importer) Conforms with CMIM Conforms with AS-I ICAO Certification	No

Pror additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.