

## Maxi free-standing Beacons / EvoSIGNAL

# Maxi Rotating 115-230VAC CL



Part No.:	262.440.60	$\overline{\alpha}$		د (ال	UK
Series:	<b>EvoSIGNAL</b>	$\mathcal{M}$	7)	C QL) US	CA

MECHANICAL DATA		
Height	173 mm	
Diameter	120 mm	
Materials	PC PC/ABS	
Dome colour	Clear	
Housing colour	Grey	
Protection category	IP66	
Connection	Push-in terminal	
cross-sectional area minimum	0,25mm <sup>2</sup> / 24AWG	
cross-sectional area maximum	1,50mm <sup>2</sup> / 16AWG	
Type of fixing	Adapter required	
Working temperature minimum	-30°C	
Working temperature maximum	+60°C	
Weight with packaging	546 g	
Product weight	446 g	

ELECTRICAL DATA		
Operating voltage	115-230V	
Operating voltage type	AC	
Operating voltage frequency	50Hz at 230V 60Hz at 115V	
Operating voltage tolerance	+/- 10%	
Rated operational voltage	230 VAC	
Rated operational current	170 mA	
Rated inrush current	<6000 mA	
Protection class	Protection class 2	
Pollution degree	3	
Overvoltage category	II	
Isolation voltage	Ui = 250V; Uimp = 2.500V	

OPTICAL DATA		
Light source	LED	
Light colour	White	
Optical signal image	Revolving	
Service life optical	50,000 h minimum	
Rotation speed (rpm)	180 U/min	
Pulse- & pause Duration [ms]	550N, 2780FF	

APPROVAL DATA	
Conforms with CE	Yes

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.




## Maxi free-standing Beacons / EvoSIGNAL

# Maxi Rotating 115-230VAC CL

Conforms with RoHS directive	Yes
WEEE	Yes
Conforms with ATEX-directive	No
Conforms with CCC	Yes
Conforms with UL	cULus
UL Type Rating	Type 12
Conforms with FCC	No
Conforms with IC	No
EAC certificate available	Yes
Conforms with UKCA (Importer)	Yes (WERMA (UK) Ltd.)
Conforms with AS-I	No
ICAO Certification	No
Conforms with DNV	No
Conforms with RoHS CN	No
Conforms with VdS	No
MTTF-value [years]	242

### **DRAWING**



For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.