## Accessories / LED Bulb LED Bulb 24VAC/DC Ø45x80



ļ

Part No.: 956.050.75

MECHANICAL DATAHeight80 mmDiameter45 mmWeight with packaging28 gProduct weight22 gELECTRICAL DATAOperating voltage12-24VOperating voltage frequency50HzOperating voltage typeAC/DCOperating voltage tolerance+/- 10%Rated operational voltage24 VDCRated operational current250 mARated operational current3 APower illuminant3 WOPTICAL DATALight sourceLEDLight sourceELELight sourceEZ7APPROVAL DATAConforms with CENoConforms with CENoConforms with CCC-ExNoConforms with CCCNoConforms with CCA (Importer)NoConforms with CCA (Importer)NoConforms with CMIMNoConforms with DNVNoConforms with DNVNoConforms with DNV <td< th=""><th colspan="2">·</th></td<>	·	
Diameter45 mmWeight with packaging28 gProduct weight22 gELECTRICAL DATAOperating voltage12-24VOperating voltage typeAC/DCOperating voltage trequency50HzOperating voltage tolerance+/- 10%Rated operational voltage24 VDCRated operational current250 mARated operational current3 APower illuminant3 WOPTICAL DATALight sourceLEDLight sourceE27APPROVAL DATAConforms with CENoConforms with ATEX-directiveNoConforms with CCC-ExNoConforms with CCCNoConforms with CCCNoConforms with FCCNoConforms with FCCNoConforms with FCCNoConforms with CCCNoConforms with CCNoConforms with CCNoConforms with CCNoConforms with CCA (Importer)NoConforms with CA </td <td colspan="2">MECHANICAL DATA</td>	MECHANICAL DATA	
Weight with packaging28 gProduct weight22 g <b>ELECTRICAL DATA</b> Operating voltage12-24VOperating voltage typeAC/DCOperating voltage trequency50HzOperating voltage tolerance+/- 10%Rated operational voltage24 VDCRated operational current250 mARated inrush current3 APower illuminant3 WOPTICAL DATALight sourceLEDLight colourWhiteOptical signal imagePermanentConforms with CENoConforms with ATEX-directiveFulfills substance restrictionWEEENoConforms with CCCNoConforms with FCCNoConforms with FCCNoConforms with FCCNoConforms with CCCNoConforms with CCNoConforms with CCNoConforms with CCNoConforms with CCA (Importer)NoConforms with CA (Importer)NoConforms with CA (Importer)NoConforms with CA (Importer)NoConforms with CA (Importer)NoConforms with CANNoConforms w	-	80 mm
Product weight22 gELECTRICAL DATAOperating voltage12-24VOperating voltage typeAC/DCOperating voltage frequency50HzOperating voltage tolerance+/- 10%Rated operational voltage24 VDCRated operational current250 mARated operational current3 APower illuminant3 WOPTICAL DATALight sourceLEDLight colourWhiteOptical signal imagePermanentLamp fitting/socketE27APPROVAL DATAConforms with CENoConforms with CENoConforms with CENoConforms with CC-ExNoConforms with CCCNoConforms with FCCNoConforms with FCCNoConforms with FCCNoConforms with ICNoConforms with ICNoConforms with KAA(Importer)NoConforms with CA (Importer)NoConforms with CA (Importer)NoConforms with ATEX-INoConforms with ATEX-INoConforms with S-INoConforms with ATEX-INoConforms with ATEX-INoConforms with CA (Importer)NoConforms with AS-INoConforms with AS-INoConforms with AS-INoConforms with DNVNoConforms with ROHS CNNo	Diameter	45 mm
ELECTRICAL DATAOperating voltage typeAC/DCOperating voltage typeAC/DCOperating voltage frequency50HzOperating voltage tolerance+/- 10%Rated operational voltage24 VDCRated operational current250 mARated inrush current3 APower illuminant3 WOPTICAL DATALight sourceLEDLight colourWhiteOptical signal imagePermanentLamp fitting/socketE27APPROVAL DATAConforms with CENoConforms with RoHS directiveFulfills substance restrictionWEEENoConforms with ATEX-directiveNoConforms with CCC-ExNoConforms with FCCNoConforms with ICNoConforms with ICNoConforms with ICNoConforms with ICNoConforms with KCA (Importer)NoConforms with ATS-INoConforms with AS-INoConforms with AS-INoConforms with NDVNoConforms with RoHS CNNo	Weight with packaging	28 g
Operating voltage12-24VOperating voltage typeAC/DCOperating voltage frequency50HzOperating voltage tolerance+/- 10%Rated operational voltage24 VDCRated operational current3 APower illuminant3 WOPTICAL DATALight sourceLEDLight colourWhiteOptical signal imagePermanentLamp fitting/socketE27APPROVAL DATAConforms with CENoConforms with ATEX-directiveFulfills substance restrictionWEEENoConforms with CCC-ExNoConforms with FCCNoConforms with FCCNoConforms with KCA (Importer)NoConforms with KCA (Importer)NoConforms with AS-INoConforms with AS-INoConforms with AS-INoConforms with DNVNoConforms with RHS CNNo	Product weight	22 g
Operating voltage typeAC/DCOperating voltage frequency50HzOperating voltage tolerance+/- 10%Rated operational voltage24 VDCRated operational current250 mARated inrush current3 APower illuminant3 WOPTICAL DATALight sourceLEDLight colourWhiteOptical signal imagePermanentLamp fitting/socketE27APPROVAL DATAConforms with CENoConforms with RoHS directiveFulfills substance restrictionWEEENoConforms with ATEX-directiveNoConforms with CCC-ExNoConforms with FCCNoConforms with ICNoConforms with ICA (Importer)NoConforms with AS-INoConforms with AS-INoConforms with DNVNoConforms with RoHS CNNo	ELECTRICAL DATA	
Operating voltage frequency50HzOperating voltage tolerance+/- 10%Rated operational voltage24 VDCRated operational current250 mARated inrush current3 APower illuminant3 WOPTICAL DATALight sourceLEDLight colourWhiteOptical signal imagePermanentLamp fitting/socketE27APPROVAL DATAConforms with CENoConforms with RoHS directiveFulfills substance restrictionWEEENoConforms with CCC-ExNoConforms with CCCNoConforms with FCCNoConforms with ICNoConforms with ICNoConforms with KCCNoConforms with ICNoConforms with UKCA (Importer)NoConforms with AS-INoICAO CertificationNoConforms with DNVNoConforms with ROHS CNNo	Operating voltage	12-24V
Operating voltage tolerance+/- 10%Rated operational voltage24 VDCRated operational current250 mARated inrush current3 APower illuminant3 WOPTICAL DATALight sourceLEDLight colourWhiteOptical signal imagePermanentLamp fitting/socketE27APPROVAL DATAVoltageConforms with CENoConforms with CENoConforms with CENoConforms with ATEX-directiveNoConforms with CCC-ExNoConforms with FCCNoConforms with FCCNoConforms with ICNoConforms with ICNoConforms with KCCNoConforms with KCCNoConforms with ICNoConforms with ICNoConforms with ICNoConforms with ICNoConforms with UKCA (Importer)NoConforms with CMIMNoConforms with AS-INoConforms with DNVNoConforms with DNVNoConforms with RoHS CNNo	Operating voltage type	AC/DC
Rated operational voltage24 VDCRated operational current250 mARated inrush current3 APower illuminant3 WOPTICAL DATALight sourceLEDLight colourWhiteOptical signal imagePermanentLamp fitting/socketE27APPROVAL DATAConforms with CENoConforms with CENoConforms with CENoConforms with ATEX-directiveFulfills substance restrictionWEEENoConforms with CCC-ExNoConforms with FCCNoConforms with FCCNoConforms with ICNoConforms with ICNoConforms with ICNoConforms with ATEX-directiveNoConforms with ATEXNoConforms with CCCNoConforms with ICNoConforms with ICNoConforms with ICNoConforms with ICNoConforms with UKCA (Importer)NoConforms with AS-INoICAO CertificationNoConforms with DNVNoConforms with RoHS CNNo	Operating voltage frequency	50Hz
Rated operational current250 mARated inrush current3 APower illuminant3 WOPTICAL DATALight sourceLEDLight colourWhiteOptical signal imagePermanentLamp fitting/socketE27APPROVAL DATAConforms with CENoConforms with CBNoConforms with ATEX-directiveFulfills substance restrictionWEEENoConforms with CCC-ExNoConforms with CCCNoConforms with FCCNoConforms with ICNoConforms with ICNoConforms with KCCNoConforms with ATEX-directiveNoConforms with CCCNoConforms with CCCNoConforms with ICNoConforms with ICNoConforms with ICNoConforms with ICNoConforms with UKCA (Importer)NoConforms with AS-INoICAO CertificationNoConforms with DNVNoConforms with RoHS CNNo	Operating voltage tolerance	+/- 10%
Rated inrush current3 APower illuminant3 WOPTICAL DATALight sourceLEDLight colourWhiteOptical signal imagePermanentLamp fitting/socketE27APPROVAL DATAConforms with CENoConforms with RoHS directiveFulfills substance restrictionWEEENoConforms with ATEX-directiveNoConforms with CCC-ExNoConforms with ICNoConforms with ICNoConforms with ICNoConforms with ULNoConforms with ICNoConforms with ICNoConforms with ICNoConforms with KCA (Importer)NoConforms with CMIMNoConforms with AS-INoConforms with DNVNoConforms with DNVNoConforms with RoHS CNNo	Rated operational voltage	24 VDC
Power illuminant3 WOPTICAL DATALight sourceLEDLight colourWhiteOptical signal imagePermanentLamp fitting/socketE27APPROVAL DATAConforms with CENoConforms with RoHS directiveFulfills substance restrictionWEEENoConforms with ATEX-directiveNoConforms with CCC-ExNoConforms with CCCNoConforms with ILNoConforms with HCCNoConforms with KCCNoConforms with SCCNoConforms with ULNoConforms with UKA (Importer)NoConforms with CMIMNoConforms with AS-INoICAO CertificationNoConforms with DNVNoConforms with RoHS CNNo	Rated operational current	250 mA
OPTICAL DATALight sourceLEDLight colourWhiteOptical signal imagePermanentLamp fitting/socketE27APPROVAL DATAConforms with CENoConforms with RoHS directiveFulfills substance restrictionWEEENoConforms with ATEX-directiveNoConforms with CCCNoConforms with CCCNoConforms with CCCNoConforms with FCCNoConforms with ICNoConforms with ICNoConforms with KCCNoConforms with ATEX-directiveNoConforms with ATEXNoConforms with ATEXNoConforms with CCCNoConforms with CCCNoConforms with KCANoConforms with FCCNoConforms with ICNoConforms with UKCA (Importer)NoConforms with AS-1NoICAO CertificationNoConforms with DNVNoConforms with DNVNoConforms with RoHS CNNo	Rated inrush current	3 A
Light sourceLEDLight colourWhiteOptical signal imagePermanentLamp fitting/socketE27APPROVAL DATAConforms with CENoConforms with RoHS directiveFulfills substance restrictionWEEENoConforms with ATEX-directiveConforms with CCC-ExNoConforms with CCC-ExNoConforms with FCCNoConforms with FCCNoConforms with FCCNoConforms with ICNoConforms with KCA (Importer)NoConforms with AS-INoICAO CertificationNoConforms with DNVNoConforms with DNVNo	Power illuminant	3 W
Light colourWhiteOptical signal imagePermanentLamp fitting/socketE27APPROVAL DATAConforms with CENoConforms with RoHS directiveFulfills substance restrictionWEEENoConforms with ATEX-directiveNoConforms with CCC-ExNoConforms with CCCNoConforms with FCCNoConforms with FCCNoConforms with FCCNoConforms with ICNoConforms with ICNoConforms with AS-INoConforms with AS-INoConforms with DNVNoConforms with DNVNoConforms with RoHS CNNo	OPTICAL DATA	
Optical signal imagePermanentLamp fitting/socketE27APPROVAL DATAConforms with CENoConforms with RoHS directiveFulfills substance restrictionWEEENoConforms with ATEX-directiveNoConforms with CCC-ExNoConforms with CCCNoConforms with FCCNoConforms with FCCNoConforms with FCCNoConforms with ICNoConforms with ICNoConforms with UKCA (Importer)NoConforms with AS-INoICAO CertificationNoConforms with DNVNoConforms with RoHS CNNo	Light source	LED
Optical signal imagePermanentLamp fitting/socketE27APPROVAL DATAConforms with CENoConforms with RoHS directiveFulfills substance restrictionWEEENoConforms with ATEX-directiveNoConforms with CCC-ExNoConforms with CCCNoConforms with FCCNoConforms with FCCNoConforms with FCCNoConforms with ICNoConforms with ICNoConforms with UKCA (Importer)NoConforms with AS-INoICAO CertificationNoConforms with DNVNoConforms with RoHS CNNo	Light colour	White
APPROVAL DATAConforms with CENoConforms with RoHS directiveFulfills substance restrictionWEENoConforms with ATEX-directiveNoConforms with CCC-ExNoConforms with CCCNoConforms with CCCNoConforms with CCCNoConforms with CCCNoConforms with PCCNoConforms with ICNoConforms with ICNoConforms with UKCA (Importer)NoConforms with AS-INoICAO CertificationNoConforms with DNVNoConforms with RoHS CNNo	Optical signal image	Permanent
Conforms with CENoConforms with RoHS directiveFulfills substance restrictionWEENoConforms with ATEX-directiveNoConforms with CCC-ExNoConforms with CCCNoConforms with CCCNoConforms with FCCNoConforms with FCCNoConforms with ICNoConforms with ULNoConforms with ICNoConforms with ICNoConforms with UKCA (Importer)NoConforms with AS-INoICAO CertificationNoICAO CertificationNoConforms with DNVNoConforms with RoHS CNNo	Lamp fitting/socket	E27
Conforms with RoHS directiveFulfills substance restrictionWEEENoConforms with ATEX-directiveNoConforms with CCC-ExNoConforms with CCCNoConforms with ULNoConforms with FCCNoConforms with ICNoConforms with ULNoConforms with ICNoConforms with ULNoConforms with ICNoConforms with UKCA (Importer)NoConforms with AS-INoICAO CertificationNoConforms with DNVNoConforms with RoHS CNNo	APPROVAL DATA	
WEEENoConforms with ATEX-directiveNoConforms with CCC-ExNoConforms with CCCNoConforms with ULNoConforms with FCCNoConforms with ICNoConforms with ICNoConforms with ULNoConforms with ICNoEAC certificate availableNoConforms with OMIMNoConforms with AS-INoICAO CertificationNoConforms with DNVNoConforms with RoHS CNNo	Conforms with CE	No
Conforms with ATEX-directiveNoConforms with CCC-ExNoConforms with CCCNoConforms with ULNoConforms with FCCNoConforms with ICNoEAC certificate availableNoConforms with UKCA (Importer)NoConforms with AS-INoICAO CertificationNoConforms with DNVNoConforms with RoHS CNNo	Conforms with RoHS directive	Fulfills substance restriction
Conforms with CCC-ExNoConforms with CCCNoConforms with ULNoConforms with FCCNoConforms with ICNoEAC certificate availableNoConforms with UKCA (Importer)NoConforms with AS-INoICAO CertificationNoConforms with DNVNoConforms with RoHS CNNo	WEEE	No
Conforms with CCCNoConforms with ULNoConforms with FCCNoConforms with ICNoEAC certificate availableNoConforms with UKCA (Importer)NoConforms with CMIMNoConforms with AS-INoICAO CertificationNoConforms with DNVNoConforms with RoHS CNNo	Conforms with ATEX-directive	No
Conforms with ULNoConforms with FCCNoConforms with ICNoEAC certificate availableNoConforms with UKCA (Importer)NoConforms with CMIMNoConforms with AS-INoICAO CertificationNoConforms with DNVNoConforms with RoHS CNNo	Conforms with CCC-Ex	No
Conforms with FCCNoConforms with ICNoEAC certificate availableNoConforms with UKCA (Importer)NoConforms with CMIMNoConforms with AS-INoICAO CertificationNoConforms with DNVNoConforms with RoHS CNNo	Conforms with CCC	No
Conforms with ICNoEAC certificate availableNoConforms with UKCA (Importer)NoConforms with CMIMNoConforms with AS-INoICAO CertificationNoConforms with DNVNoConforms with RoHS CNNo	Conforms with UL	No
EAC certificate availableNoConforms with UKCA (Importer)NoConforms with CMIMNoConforms with AS-INoICAO CertificationNoConforms with DNVNoConforms with RoHS CNNo	Conforms with FCC	No
Conforms with UKCA (Importer)NoConforms with CMIMNoConforms with AS-INoICAO CertificationNoConforms with DNVNoConforms with RoHS CNNo	Conforms with IC	No
Conforms with CMIMNoConforms with AS-INoICAO CertificationNoConforms with DNVNoConforms with RoHS CNNo	EAC certificate available	No
Conforms with CMIMNoConforms with AS-INoICAO CertificationNoConforms with DNVNoConforms with RoHS CNNo	Conforms with UKCA (Importer)	No
ICAO Certification No Conforms with DNV No Conforms with RoHS CN No	• •	No
Conforms with DNV No Conforms with RoHS CN No	Conforms with AS-I	No
Conforms with DNV No Conforms with RoHS CN No	ICAO Certification	No
Conforms with RoHS CN No	Conforms with DNV	
	Conforms with RoHS CN	No
	Conforms with VdS	No

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.